MATERIAL SAFETY DATA SHEET

Share Corporation P.O. Box 245013 Milwaukee, WI 53224

GENERAL INFORMATION NUMBER: (414) 355-4000 EMERGENCY TELEPHONE NUMBER: (800) 776-7192

CHEMTREC: (800) 424-9300



REVISION DATE: October 31, 2007 DATE OF ISSUE: October 31, 2007

I - Product Identification

Battery Cleaner

PRODUCT CODE: 8205

CHEMICAL FORMULATION: Pressurized water based alkaline cleaner.

REACTIVITY: 0 NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 1 FLAMMABILITY: 2 0 - Insignificant 2 - Moderate; 1 - Slight; HAZARD RATING: 4 - Extreme; 3 - High;

II - Hazardous Ingredients Values reported as TWA unless noted. APPROX **OSHA ACGIH** EPA 40 CFR: % PEL TLV 372 CAS# SUBSTANCE 302 355 N/D N/E 800 ppm N 106-97-8 Butane N 114-55-8 Sodium Bicarbonate N/D N/E N/E N

STEL: Short Term Exposure Limit PEL: Permissible Exposure Limit N/D: Not Determined N/E: Not Established Y: Yes N: No N/A: Not Applicable

302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).

355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355). 372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - Physical Data

SPECIFIC GRAVITY (WATER = 1): 0.93 ± 0.05 BOILING POINT (°F): < 0 to 212

VAPOR PRESSURE (mm Hg): N/D VOC CONTENT (% by weight): N/D

EVAPORATION RATE (WATER = 1): N/D VAPOR DENSITY (AIR = 1): N/D

SOLUBILITY IN WATER: N/D **pH**: 9.25 ± 0.5

APPEARANCE AND ODOR: Yellow foam, characteristic odor. *Tested using the liquid component (excluding the propellant).

IV - Fire and Explosion Hazard Data

FLAME EXTENSION: N/D FLASH POINT (°F): 125* (TEST METHOD): Closed cup NFPA 30B Rating: N/D

LOWER: 1.9 FLAMMABLE LIMITS IN AIR (VOLUME %) **UPPER: 12.7**

EXTINGUISHING MEDIA: Water fog, carbon dioxide, dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water fog. Firefighters should be equipped with full protective gear including self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARD: Exposure to temperature above 120°F may cause bursting.

V - Reactivity Data

STABILITY: Stable

INCOMPATIBILITY: Strong oxidizers and acids. CONDITIONS TO AVOID: High temperatures.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce oxides of carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: None

VI - Health Hazard Data

ROUTES OF ENTRY INHALATION: X EYE CONTACT: X SKIN CONTACT: X INGESTION: X INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS: None EFFECTS OF OVEREXPOSURE

IF IN EYES: Will cause redness and burning sensation.

IF ON SKIN: Will cause deffating of skin. Effects are reversible.

IF SWALLOWED: Aspiration hazard if swallowed.

IF INHALED: Irritation of respiratory tract, headache, dizziness, nausea and loss of coordination. Extreme overexposure may result in unconsciousness and possibly death.

EMERGENCY AND FIRST AID PROCEDURES

IF IN EYES: Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

IF ON SKIN: Flush with large quantities of water. Remove contaminated clothing and launder separately before reuse. If irritation persists, obtain medical attention.

IF SWALLOWED: Contact physician or poison control center immediately. Do not induce vomiting.

IF INHALED: Remove person to fresh air. If irritation persists, give oxygen. Get medical attention.

VII - Spill or Leak Protection

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Ventilate area and remove all sources of ignition. Contain spill. Soak up spilled material with inert absorbent material and place in a properly marked closed container for proper disposal. WASTE DISPOSAL METHOD: Consult local environmental authorities. Dispose of cans in non-incinerated trash only.

VIII - Special Protection Information

RESPIRATORY PROTECTION: Use with adequate ventilation. If recommended Exposure Limits are exceeded wear a NIOSH approved respirator, following manufacturer's recommendations.

VENTILATION LOCAL: Recommended PROTECTIVE GLOVES: None required if spraying.

EYE PROTECTION: Safety glasses or chemical splash goggles.

OTHER PROTECTIVE EQUIPMENT: Long sleeves and long pants.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place away from heat or open flame. Do not expose to direct sunlight or store at temperatures above 120°F.

OTHER PRECAUTIONS: Keep out of reach of children. Do not puncture or incinerate container.

IX - Transportation Information (ground transportation only)

DOT ID NUMBER: None DOT CLASS: ORM-D DOT PROPER SHIPPING NAME: Consumer Commodity

DOT PACKING GROUP: None

The shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.

REVISION DATE: October 31, 2007

Prepared by: Technical Dept.

DATE OF ISSUE: October 31, 2007

MECHANICAL: Not required

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Share Corporation assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.