

SAFETY DATA SHEET

Creation Date 26-Sep-2009 Revision Date 02-Feb-2015 Revision Number 1

1. Identification

Product Name 2-Chlorobutane

Cat No.: AC108830000; AC108830010; AC108830050; AC108832500

Synonyms sec-Butyl chloride

Recommended Use Laboratory chemicals.

Uses advised against No Information available

Details of the supplier of the safety data sheet

Company Entity / Business Name

Acros Organics One Reagent Lane

Fair Lawn, NJ 07410 Fair Lawn, NJ 07410 Tel: (201) 796-7100

CHEMTREC Tel. No.US:001-800-424-9300 /

Europe:001-703-527-3887

Europe: +32 14 57 52 99

Emergency Telephone Number

/ Europe call: +32 14 57 52 11

For information US call: 001-800-ACROS-01

Emergency Number **US:**001-201-796-7100 /

2. Hazard(s) identification

Classification

Fisher Scientific

One Reagent Lane

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 2

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor



Precautionary Statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep cool

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None identified

3. Composition / information on ingredients

Component	CAS-No	Weight %
Butane, 2-chloro-	78-86-4	99

4. First-aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Obtain medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Obtain medical attention.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial

respiration. Obtain medical attention.

Ingestion Do not induce vomiting. Obtain medical attention.

Most important symptoms/effects Breathing difficulties. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water spray. Carbon dioxide (CO2). Dry chemical. chemical foam.

Unsuitable Extinguishing Media No information available

Flash Point -15 °C / 5 °F

Method - No information available

Autoignition Temperature

Explosion Limits

460 °C / 860 °F

Upper 8.8% **Lower** 1.7%

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Hydrogen chloride gas Carbon monoxide (CO) Carbon dioxide (CO2)

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full

Revision Date 02-Feb-2015 2-Chlorobutane

protective gear.

NFPA

Health **Flammability** Instability Physical hazards N/A

Accidental release measures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of **Personal Precautions**

Environmental Precautions Should not be released into the environment.

Methods for Containment and Clean Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Provide adequate ventilation.

7. Handling and storage

Ensure adequate ventilation. Wear personal protective equipment. Avoid contact with skin Handling

and eyes. Do not breathe vapors or spray mist. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Empty containers retain product residue, (liquid and/or

vapor), and can be dangerous.

Storage Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Flammables

area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

8. Exposure controls / personal protection

Exposure Guidelines This product does not contain any hazardous materials with occupational exposure limits

established by the region specific regulatory bodies.

Use explosion-proof electrical/ventilating/lighting/equipment. **Engineering Measures**

Personal Protective Equipment

Flammability or explosive limits

Wear appropriate protective eyeglasses or chemical safety goggles as described by **Eye/face Protection**

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Wear appropriate protective gloves and clothing to prevent skin exposure. Skin and body protection

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

> EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Handle in accordance with good industrial hygiene and safety practice. **Hygiene Measures**

Physical and chemical properties

Physical State Liquid **Appearance** Clear Odor Strong

Odor Threshold No information available No information available

Melting Point/Range -140 °C / -220 °F

Boiling Point/Range 68 - 70 °C / 154.4 - 158 °F @ 760 mmHg

Flash Point -15 °C / 5 °F

Evaporation Rate No information available Flammability (solid.gas) No information available

Revision Date 02-Feb-2015 2-Chlorobutane

Upper 8.8%

Lower 1.7% **Vapor Pressure** 145 mbar @ 20 °C 3.2 (Air = 1.0)**Vapor Density** 0.870 **Relative Density**

Solubility No information available Partition coefficient; n-octanol/water No data available 460 °C / 860 °F **Autoignition Temperature Decomposition Temperature** No information available

Molecular Formula C4 H9 CI 92.57 **Molecular Weight**

10. Stability and reactivity

No information available

Reactive Hazard None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Incompatible products.

Incompatible Materials Strong oxidizing agents, Strong bases, Metals, copper

Hazardous Decomposition Products Hydrogen chloride gas, Carbon monoxide (CO₂), Carbon dioxide (CO₂)

Hazardous Polymerization No information available.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Viscosity

Product Information No acute toxicity information is available for this product

Component Information

Component LD50 Oral		LD50 Oral	LD50 Dermal	LC50 Inhalation
	Butane, 2-chloro-	20 mL/kg (Rat)	20 mL/kg (Rabbit)	Not listed
	Toxicologically Synergistic	No information available		

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation May cause eye, skin, and respiratory tract irritation

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

	Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Ī	Butane, 2-chloro-	78-86-4	Not listed				

Mutagenic Effects No information available

No information available. **Reproductive Effects**

Developmental Effects No information available.

No information available. **Teratogenicity**

STOT - single exposure None known STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects.both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness.

delayed tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated. See actual entry in RTECS for

complete information.

12. Ecological information

Ecotoxicity

Do not empty into drains.

Persistence and Degradability
Bioaccumulation/ Accumulation

No information available.

No information available.

No information available.

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN1127

Proper Shipping NameCHLOROBUTANESProper technical name2-Chlorobutane

Hazard Class 3 Packing Group II

<u>TDG</u>

UN-No UN1127

Proper Shipping Name CHLOROBUTANES

Hazard Class 3
Packing Group ||

<u>IATA</u>

UN-No UN1127

Proper Shipping Name CHLOROBUTANES

Hazard Class 3 Packing Group II

IMDG/IMO

UN-No UN1127

Proper Shipping Name CHLOROBUTANES

Hazard Class 3
Packing Group ||

15. Regulatory information

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Butane, 2-chloro-	Х	Χ	-	201-151-7	-		Χ	Χ	Χ	Х	-

Legend:

X - Listed

- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313 Not applicable

SARA 311/312 Hazardous Categorization

Acute Health Hazard No
Chronic Health Hazard No
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

Clean Water Act Not applicable

Clean Air Act Not applicable

OSHA Occupational Safety and Health Administration

Not applicable

CERCLA

Not applicable

California Proposition 65

This product does not contain any Proposition 65 chemicals

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Butane, 2-chloro-	X	X	X	-	-

U.S. Department of Transportation

Reportable Quantity (RQ):

DOT Marine Pollutant

N

N

N

N

N

N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class B2 Flammable liquid



16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 26-Sep-2009

 Revision Date
 02-Feb-2015

 Print Date
 02-Feb-2015

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS)

Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of SDS