

## SAFETY DATA SHEET

### SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

Product Identifier : **HENRY® EASYRELEASE Adhesive Remover**  
Product ID No. : 70010862  
Trade Name/Synonyms : HENRY EasyRelease  
Material Use : Concentrated Adhesive Remover.  
Uses Advised Against : Use only as recommended in the product's Technical Data Sheet.  
**Manufacturer's name and address:**



ARDEX L.P.  
400 Ardex Park Dr.  
Aliquippa, PA 15001 USA

Information Telephone No. : (724) 203-8000  
Website Address : <http://www.wwhenry.com>  
24 Hr Emergency Telephone # : CHEM-TEL: 1-800-255-3924 OR 1-813-248-0585 (call collect)

### SECTION 2 – HAZARDS IDENTIFICATION

**GHS Classification per 29 CFR 1910.1200 (OSHA HCS 2012) and HPR (WHMIS 2015)**

Skin corrosion/irritation, Category 1  
Serious eye damage/eye irritation, Category 1  
Acute Toxicity, Dermal, Category 4  
Acute Toxicity, Inhalation, Category 4  
Specific Target Organ Toxicity, Single Exposure, Category 3, Respiratory

**GHS Pictograms**



**Signal Word**

Danger!

**Hazard Statements**

Causes severe skin burns and eye damage.  
Harmful if inhaled.  
Harmful in contact with skin.  
May cause respiratory irritation.

**Precautionary Statements**

Do not breathe vapors. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection. Wash hands and exposed skin thoroughly after handling. Wash contaminated clothing before reuse. Store in a well-ventilated place. Keep container tightly closed. Keep out of the reach of children. Store locked up. Dispose of contents / container in accordance with federal, state, and local laws. Do not allow product to enter drains.

**Hazards Not Otherwise Classified**

None.

**% with Unknown Acute Toxicity**

Less than 15% of this product consists of ingredients with unknown acute toxicity.

### SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS #	% (by weight)
2-Butoxyethanol	111-76-2	7 – 13
Ethanolamine	141-43-5	7 – 13

The exact percentages of the ingredients have been withheld by the manufacturer as trade secrets.

### SECTION 4 – FIRST AID MEASURES

<b>General</b>	: IF exposed or concerned: Get medical advice/attention. Show product label or Safety Data Sheet to medical personnel. Symptoms may be delayed. Treat exposures immediately to prevent harm.
<b>Inhalation</b>	: If inhaled, remove person to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention/advice immediately.
<b>Skin contact</b>	: Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Seek medical attention/advice.
<b>Eye contact</b>	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
<b>Ingestion</b>	: Rinse mouth. Do NOT induce vomiting. Get medical advice/attention.
<b>Notes for Physician</b>	: Treat symptomatically.

**Signs and symptoms of short-term (acute) exposure**

<i>Inhalation</i>	: Inhalation of vapors could cause respiratory irritation. Symptoms may include coughing and shortness of breath.
<i>Skin</i>	: Causes skin burns. Symptoms may include redness, itching, and pain.
<i>Eyes</i>	: Causes eye burns. Symptoms may include redness, itching, tearing, blurry vision, and pain. May cause blindness if not treated promptly.
<i>Ingestion</i>	: Causes burns to the mouth, throat, and digestive tract. Symptoms such as gastric pain, nausea, vomiting, and diarrhea may occur.

**Effects of long-term (chronic) exposure**

- : Long-term (chronic) exposure causes the same symptoms as short term (acute) exposure by each exposure route.

**Indication of need for immediate medical attention or special treatment**

- : Difficulty breathing after exposure to vapors.
- : Any exposure to the eye which causes irritation or damage.
- : Exposure to the skin that causes a chemical burn.

### SECTION 5 – FIRE FIGHTING MEASURES

<b>Suitable extinguishing media</b>	: Carbon dioxide, dry chemical powder, foam or water spray.
<b>Unsuitable extinguishing media</b>	: Water jet. May spread fire.
<b>Hazardous combustion products</b>	: Carbon monoxide, carbon dioxide, nitrogen oxides (NO <sub>x</sub> ) and other toxic vapors and gases which are common to thermal degradation of organic compounds.
<b>Special fire-fighting procedures/equipment</b>	: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. After fires have been extinguished, carefully clean all equipment and surfaces exposed to fumes.
<b>Environmental precautions</b>	: Do not allow this product to enter drains.

**Fire hazards/conditions of flammability**

- : Not flammable under normal conditions of use. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure. Ammonia gas may be liberated at high temperatures.

**Flammability classification (OSHA 29 CFR 1910.1200, WHMIS 2015)**

- : Not flammable under normal conditions of handling.

**NFPA Rating**

- : 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

*Health: 3 Flammability 0 Instability 0 Special Hazards: None*

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

**Personal precautions**

- : See Section 7 for safe handling procedures. Wear chemically resistant personal protective equipment during cleanup. Restrict access to area until completion of clean-up. All persons dealing with clean-up must be properly trained and wear the appropriate chemically protective equipment. Wear appropriate personal protective equipment to prevent contact with material during clean-up procedure, including impervious gloves and safety glasses. Refer to Section 8 for additional information on acceptable personal protective equipment.

**Environmental precautions**

- : Do not this material to enter drains or waterways. Do not allow material to contaminate ground water system.

**Emergency Procedures**

- : This product does not contain chemicals requiring EPA notification for spills. In case of a chemical spill, call the emergency telephone number listed in Section 1. US CERCLA Reportable quantity (RQ): None reported.

**Methods and materials for containment and cleaning up**

- : Ventilate area of release. Stop spill or leak at source if safely possible. Contain product with inert absorbent material, preventing it from entering sewer lines or waterways. Gather up spilled material and place in suitable container for later disposal (see Section 13). Residual of product, while still wet, can be cleaned up with warm water. Notify the appropriate authorities as required.

**Prohibited materials**

- : None known.

**Reference to other sections**

- : See Section 13 for disposal information.

## SECTION 7 – HANDLING AND STORAGE

**Safe handling procedures**

- : Do not get in eyes, on skin, or on clothing. Do not breathe vapors or mists of this product. Do not swallow. Observe good hygiene standards. Wash hands and exposed skin thoroughly after handling. Wear glove, safety glasses, and protective clothing. Use only with adequate ventilation. Promptly remove any clothing that becomes contaminated. Clean contaminated clothing before reuse. Keep container tightly closed.

**Storage requirements**

- : Store in a cool, dry, well-ventilated area. Keep tightly closed when not in use. Store the product in its original container. Thoroughly rinse empty container before disposal.

**Incompatible materials**

- : See Section 10.

**Special packaging materials**

- : Always keep in containers made of the same materials as the supply container.

## SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

**Permissible Exposure Limits**

- : No exposure limits have been established for the product itself. Below are exposure limits for the components in the product.

Ingredients	CAS #	ACGIH TLV		OSHA PEL	
		TWA	STEL	PEL	STEL
2-Butoxyethanol	111-76-2	20 ppm	N/Av	50 ppm (skin)	N/Av
Ethanolamine	141-43-5	3 ppm	6 ppm	3 ppm	6 ppm

**Engineering Controls**

- : Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Ventilation should effectively remove and prevent buildup of any vapor generated from the handling of this product.

#### Personal Protection Equipment

- Eye / face protection** : Chemical goggles or safety glasses, as appropriate for the job. If splashing is likely, wear a full face shield.
- Skin protection** : Wear gloves which are impervious to the material. Glove materials such as nitrile rubber or Viton (fluorocarbon rubber) are recommended. Consult with glove manufacturers regarding breakthrough time for this material.
- Body protection** : Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact.
- Respiratory protection** : If work process generates excessive quantities of vapor or dust, or exposures in excess of any PEL, wear an appropriate organic vapor respirator.

**Site safety equipment** : An eyewash station and safety shower should be made available in the immediate working area.

**General hygiene considerations** : Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mist. Upon completion of work, wash hands thoroughly. Remove contaminated clothing and wash it thoroughly before reuse. Clean all equipment and clothing at end of each work shift.

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state</b>	: Liquid	<b>Appearance</b>	: Pale amber
<b>Odor</b>	: Ammonia	<b>Odor threshold</b>	: N/Av
<b>pH</b>	: 12.1	<b>Specific gravity</b>	: 1.05
<b>Boiling point</b>	: > 212°F (100°C)	<b>Coefficient of water/oil distribution</b>	: N/Av
<b>Melting/Freezing point</b>	: N/Av	<b>Solubility in water</b>	: Miscible
<b>Vapor pressure (mm Hg @ 20°C / 68°F)</b>	: N/Av	<b>Evaporation rate (n-Butyl acetate = 1)</b>	: N/Av
<b>Vapor density (Air = 1)</b>	: N/Av	<b>Volatiles (% by weight)</b>	: > 95 % (includes water)
<b>Volatile organic compounds (VOCs)</b>	: 4.4%, per CARB regulations, after recommended dilution		
<b>Particle size</b>	: N/Av	<b>Flammability classification</b>	: Not flammable
<b>Flash point</b>	: >93.3°C (200°F)	<b>Lower flammable limit (% by vol)</b>	: Not available
<b>Flash point method</b>	: Setaflash closed	<b>Upper flammable limit (% by vol)</b>	: Not available
<b>Auto-ignition temperature</b>	: N/Av	<b>Decomposition temperature</b>	: Not available
<b>Viscosity</b>	: Not available	<b>Oxidizing properties</b>	: Not available
<b>Explosion data: Sensitivity to mechanical impact / static discharge</b>			
: Not expected to be sensitive to mechanical impact or static discharge.			

## SECTION 10 – REACTIVITY AND STABILITY INFORMATION

<b>Reactivity</b>	: Not reactive.
<b>Stability</b>	: Stable under the recommended storage and handling conditions prescribed.
<b>Hazardous reactions</b>	: Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	: High temperatures.
<b>Materials to avoid and incompatibility</b>	: Strong oxidizing agents; Acids.
<b>Hazardous decomposition products</b>	
: None known, refer to hazardous combustion products in Section 5.	

## SECTION 11 – TOXICOLOGICAL INFORMATION

<b>Routes of exposure</b>	: <i>Inhalation</i> : YES <i>Skin Absorption</i> : YES <i>Skin and Eyes</i> : YES <i>Ingestion</i> : YES
<b>Symptoms of exposure</b>	: See Section 4.
<b>Acute Toxicity Estimate</b>	: Acute Toxicity Estimate (ATE) is a calculated estimate of the acute toxicological properties of a mixture, based on the LC50 and LD50s of the ingredients and their respective weight fractions of the mixture. It provides information when test data is

not available for the mixture itself. See 29 CFR 1910.1200, Appendix A, paragraph A.1.3.6.2 for a description of the ATE.

ATE Inhalation, 4 hr, rat : > 16 mg/L  
ATE Oral, rat : > 3000 mg/kg  
ATE Dermal, rabbit : > 1600 mg/kg

**Toxicological data** : See below for individual ingredient acute toxicity data.

Ingredients	LC50 (4 hr)	LD50	
	Inhalation, rat, mg/L	Oral, rat, mg/kg	Dermal, rabbit, mg/kg
2-Butoxyethanol	2.17	917	N/Av
Ethanolamine	N/Av	1089	1015

**Skin corrosion or irritation** : Corrosive to skin.

**Serious eye damage / eye irritation** : Corrosive to eyes. Could cause permanent damage to eyes, including blindness.

**Respiratory or skin sensitization** : Not expected to cause skin or respiratory sensitization reactions.

**Germ cell mutagenicity** : None known.

**Carcinogenic status** : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

**Reproductive toxicity** : None known.

**Specific Target Organ Toxicity, Single Exposure**

: May cause respiratory irritation.

Overexposure to concentrated 2-Butoxyethanol is known to cause Central Nervous System effects (headache, dizziness, drowsiness, nausea), especially via absorption through the skin. Due to its low concentration in this product, 2-Butoxyethanol is unlikely to cause these symptoms under normal conditions of use.

**Specific Target Organ Toxicity, Repeated Exposure**

: None known.

**Aspiration hazard** : None known.

**Additional information** : N/Av

## SECTION 12 – ECOLOGICAL INFORMATION

**Environmental effects** : The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

**Ecotoxicity** : No data available.  
**Biodegradability** : No data available.  
**Bioaccumulative potential** : No data available.  
**Mobility in soil** : No data available.  
**PBT and vPvB assessment** : No data available.  
**Other adverse effects** : No data available.

## SECTION 13 – DISPOSAL CONSIDERATION

**Handling for disposal** : Handle waste according to recommendations in Section 7.



**Methods of disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.

**Packaging** : Handle contaminated packaging in the same manner as the product.

**RCRA** : For disposal of unused or waste material, check with local, state and federal environmental agencies.

## SECTION 14 – TRANSPORTATION INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
------------------------	-----------	---------------	-------	---------------	-------

<b>US DOT</b>	<b>UN 2491</b>	ETHANOLAMINE SOLUTIONS	<b>8</b>	<b>III</b>	
<b>49 CFR/DOT Additional Information</b>	May be shipped as Limited Quantity when transported in containers no larger than 5.0 Liters (1.3 Gallons); in packages not exceeding 30 kg gross mass. Refer to 49 CFR 173.154.				
<b>CAN TDGR</b>	<b>UN 2491</b>	ETHANOLAMINE SOLUTIONS	<b>8</b>	<b>III</b>	
<b>TDGR Additional Information</b>	May be shipped as Limited Quantity when transported in containers no larger than 5.0 Litres; in packages not exceeding 30 kg gross mass. Refer to TDG Part 1: 1.11, 1.17; and Schedule 1, Column 6(a).				

**IATA**

**UN No** : UN2491  
**Proper Shipping Name** : ETHANOLAMINE SOLUTIONS  
**Hazard Class** : Class 8  
**Packing Group** : PG III

**IMDG**

**UN No** : UN2491  
**Proper Shipping Name** : ETHANOLAMINE SOLUTIONS  
**Hazard Class** : Class 8  
**Packing Group** : PG III

## SECTION 15 – REGULATORY INFORMATION

**Canadian Information:**

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR). This SDS contains all of the information required by the HPR.

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

**US Federal Information:**

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): none reported.

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: This product does not contain an Extremely Hazardous Substance under SARA Section 302.

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes:

Skin corrosion/irritation, Category 1  
 Serious eye damage/eye irritation, Category 1  
 Acute Toxicity, Dermal, Category 4  
 Acute Toxicity, Inhalation, Category 4  
 Specific Target Organ Toxicity, Single Exposure, Category 3, Respiratory

Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The threshold for this product is 10,000 pounds.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This product is not subject to SARA notification requirements, since it contains no Toxic Chemical constituents above their *de minimus* concentrations.

**U.S. State Right to Know Laws**

California Proposition 65: See product label for information regarding Proposition 65.

Other State Right to Know Laws:

Ingredient	CAS NO.	CA	MA	MN	NJ	NY	PA	RI
2-Butoxyethanol	111-76-2	YES	YES	YES	YES	No	YES	YES
Ethanolamine	141-43-5	YES	YES	No	YES	No	YES	YES

## SECTION 16 – OTHER INFORMATION

HMIS Rating : \* - Chronic Hazard 0 - Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Severe  
Health: 3 Flammability 0 Physical Hazard: 0 PPE: Gloves, safety glasses

Legend : ACGIH: American Conference of Governmental Industrial Hygienists  
CAS: Chemical Abstract Services  
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980  
CFR: Code of Federal Regulations  
DOT: Department of Transportation  
DSL: Domestic Substances List  
EPA: Environmental Protection Agency  
GHS: Globally Harmonized System  
HPR: Hazardous Products Regulations  
IARC: International Agency for Research on Cancer  
Inh: Inhalation  
N/Av: Not Available  
N/Ap: Not Applicable  
NIOSH: National Institute of Occupational Safety and Health  
NTP: National Toxicology Program  
OSHA: Occupational Safety and Health Administration  
PEL: Permissible exposure limit  
RCRA: Resource Conservation and Recovery Act  
SARA: Superfund Amendments and Reauthorization Act  
STEL: Short Term Exposure Limit  
TDG: Canadian Transportation of Dangerous Goods Act & Regulations  
TLV: Threshold Limit Values  
TSCA: Toxic Substance Control Act  
TWA: Time Weighted Average  
WHMIS: Workplace Hazardous Materials Identification System

### Disclaimer of Liability

The Information presented herein is supplied as a guide to those who handle or use this product and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive. The manner and conditions of use and handling may involve other and additional considerations. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

No warranty of any kind is given or implied. ARDEX L.P. will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information contained herein.

Prepared By:  
ARDEX L.P.  
400 Ardex Park Drive  
Aliquippa, PA, U.S.A.  
15001

(724) 203-8000  
Visit our Website: <http://www.wwhenry.com>

Revision date: : 11-Oct-2021

End of Document