

SAFETY DATA SHEET (SDS)

SHEET 1 OF 4

PRIME LINE PRODUCTS, INC. 26950 SAN BERNARDINO AVE. REDLANDS, CA 92374

PH: 909-887-8118 FX: 909-880-2906 Email: info@prime-line-products.com HEALTH 1 EXPOSURE MAY CAUSE INCAPACITATION

FIRE 4 HIGHLY FLAMMABLE MATERIAL

REACTIVITY 0 NORMALLY STABLE

SPECIFIC

EMERGENCY #: 800-255-3924, 909-887-8118

SECTION 1: P	RODUCT IDEN	ITIFICAT	TON			
PRODUCT NAME	RZ-50 AEROSOL SP	RAY LUBRIC	CANT PRODUC	T DESCRIPT	TON PTFE POLYMER DRY FILM AEROSOL LUBRICANT	
PRODUCT PART NO.	RZ 50	TD	DADE NAMES	DD 50 D750		
PRODUCT CLASS	LUBRICANT	IN	RADE NAMES	RD-50, RZ50		
C.A.S. NUMBER		SDS R	SDS REVISION LEVEL REV REV DATE			
SDS NUMBER	RZ-50	REV			APPLICATIONS REQUIRING LUBRICATION	
SDS DATE	2/18/2015	D	8/25/2016			
SECTION 2: H	AZARDS IDEN	TIFICAT	ION			
EYE		SLIGHT	TLY IRRITATING BU	DOES NOT	CAUSE EYE TISSUE INJURY	
SKIN CONTACT	LOW ORDER OF TOXICITY. FREQUENT OR PROLONGED CONTACT MAY IRRITATE AND/OR CAUSE DERMATITIS OR AGGRAVATE AN EXISTING CONDITION.					
SKIN ABSORPTION	THIS MATERIAL IS AN ASPIRATION HAZARD AND DEFATS THE SKIN.					
INGESTION	SMALL AMOUNTS OF THIS PRODUCT ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION OR VOMITING MAY CAUSE MILD TO SERVERE PULMONARY INJURY-POSSIBLE MINIMAL TOXICITY.					
INHALATION	HIGH VAPOR/AEROSOL CONCENTRATIONS, GREATER THAN 100PPM, ARE IRRITATING TO THE EYES AND RESPIRATORY TRACT, MAY CAUSE HEADACHES, DIZZINESS, ANESTHESIA, DROWSINESS, UNCONSCIOUSNESS AND OTHER CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING DEATH. BREATHING VAPORS OF HIGH CONCENTRATIONS MAY CAUSE CNS DEPRESSION.					
ACUTE EFFECTS	NA					
CHRONIC EFFECTS	NA					
CARCINOGENIC	NA					

All materials used in the manufacture of the above product are compliant with the European Union Directive 2002/95/EC for the Restriction of the use of certain Hazardous Substances in Electrical and Electronic Equipment (RoHS). No Lead (Pb), Cadmium (Cd), Mercury (Hg), Hexavalent Chromium (Cr+6), PBB or PBDE is intentionally added to these components. Any trace impurities of these substances contained in the components are below the RoHS specified threshold level.



The Replacement Hardware Company

SAFETY DATA SHEET (SDS)

PRIME LINE PRODUCTS, INC. 26950 SAN BERNARDINO AVE. REDLANDS, CA 92374

PH: 909-887-8118
FX: 909-880-2906
Email: info@prime-line-products.com

()	
PRODUCT NAME	RZ-50 AEROSOL SPRAY LUBRICANT
PRODUCT PART NO.	RZ 50
PRODUCT DESC.	PTFE POLYMER DRY FILM AEROSOL LUBRI
PRODUCT CLASS	LUBRICANT
C.A.S. NUMBER	0
SDS NUMBER	RZ-50
SDS DATE	2/18/2015

SHEET 2 OF 4

	EMERGENCY		#: 800-255-	SDS NUMBER		RZ-50 2/18/2015	
		<i>3924, 909</i>	<i>3924, 909-887-8118</i>				
SECTION 3: CC	MPOSITION / IN	FORMATION O	N INGREDIENT	S			
			2.20	CONTENT EXPOSURE LIMITS		RE LIMITS	
	CHEMICAL NAME		CAS#	WEIGHT %	ACGIH	TLV	OSHA PEL
ALIPHATIC HYDROCA	RBON		142-82-5	40-60	500 PPM 400 PPM		
CERFLON® IPA DISPE	RSION			4-8 NOT ESTABLISHED NOT ESTABLISHE			
HYDROCARBON PROPELLANT			68476-86-8	40-60	800 PPM		800 PPM
SECTION 4: FIF	RST AID MEASUI	RES					
EYE CONTACT	FLUSH EYES WITH LA	RGE AMOUNTS OF WA	ATER UNTIL IRRITATION		S. IF IRRITATI	ON PERS	ISTS, SEEK MEDICA
SKIN CONTACT	FLUSH WITH LARGE AMOUNTS OF WATER, USE SOAP IF NECESSARY. REMOVE GROSSLY CONTAMINATED CLOTHING, INCLUDING SHOES, AND LAUNDER BEFORE REUSE.						
SKIN ABSORPTION	NA						
INGESTION	IF SWALLOW	/ED, DO NOT INDUCE \	OMITING. KEEP AT R	REST AND SE	EK MEDICAL	PROMPT	ATTENTION
INHALATION	USE PROPER RESPIRATORY PROTECTION AND IN A WELL VENTILATED AREA. REMOVE VICTIM FROM EXPOSURE AND GENERAL AREA. ADMINISTER ARTIFICIAL RESPIRATION IF BREATHING IS STOPPED. KEEP AT REST AND SEEK PROMP MEDICAL ATTENTION.						
SECTION 5: FIF	RE-FIGHTING ME	EASURES					
	FLAMMABLE LIMITS (% B'				BY VOLUME)		
FLASH POINT	-104 ⁰ C, 169 K	AUTOIGNITION TEMP	540 ⁰ C, 813 K	IN AIR	LEL	-	UEL
				IN AIR	2.379	%	9.50%
EXTINGUISHING MEDIA	STOP GAS FLO	W. RECOMMEND US	E OF DRY CHEMICAL,	CO₂ OR HAL	OGENATED E	XTINGUIS	SHING AGENT.
SPECIAL FIRE FIGHTING PROCEDURES	THE GAS SOURCE CANN WITH WATER TO PREVE SHUT OFF. ISOLATE	MMEDIATELY BEFORE AT NOT BE SHUT OFF IMMED NT OVER-HEATING, FLAS THE "FUEL" SUPPLY FRO R. USE PROPER PROTEC CONCI	NATELY, ALL EQUIPMENT SH-BACKS AND/OR EXPLO OM FIRE. AVOID SPRAYII	TAND SURFAC OSIONS. CON' NG WATER DIF RESH AIR RES	ES EXPOSED T FROL THE FIRE RECTLY INTO S PIRATORS WH	O THE FIRE UNTIL THE	E SHOULD BE COOLED E GAS SUPPLY CAN BE ONTAINERS DUE TO
UNUSUAL FIRE & EXPLOSION HAZARDS	WITH AIR AND WILL BURN	LAMMABLE VAPORS AT V N IN THE OPEN AND CAN TRAVEL LONG DISTANC	BE EXPLOSIVE IN CONFI	NED SPACES. ON. ALKANE/O	PRODUCT VAF	PORS ARE	INVISIBLE AND HEAVIE

EXPLOSIONS.



SAFETY DATA SHEET (SDS)

SHEET 3 OF 4

PRIME LINE PRODUCTS, INC. 26950 SAN BERNARDINO AVE. REDLANDS, CA 92374 PH: 909-887-8118 FX: 909-880-2906

Email: info@prime-line-products.com EMERGENCY #: 800-255-3924, 909-887-8118

()	
PRODUCT NAME	RZ-50 AEROSOL SPRAY LUBRICANT
PRODUCT PART NO.	RZ 50
PRODUCT DESC.	PTFE POLYMER DRY FILM AEROSOL LUBRI
PRODUCT CLASS	LUBRICANT
C.A.S. NUMBER	0
SDS NUMBER	RZ-50
SDS DATE	2/18/2015

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACTIONS TO TAKE FOR LEAK OR SPILLS	SPILLS SHOULD BE ABSORBED OR SCRAPED UP. AVOID WATER CONTAMINATION.
WASTE DISPOSAL	EMPTY DEPRESSURIZED CONTAINERS CANNOT BE REUSED. CANS WHICH ARE PRESSURIZED OR CONTAIN LIQUID MUST BE DISPOSED IN A PERMITTED WASTE MANAGEMENT FACILITY. DISPOSAL MUST BE IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS. INCINERATION EQUIPMENT SHOULD BE CAPABLE OF HANDLING LARGE VOLUMES OF DENSE BLACK SMOKE AND WITHSTAND THE CORROSIVE EFFECTS OF ACID CASES. THESE MATERIALS ARE NOT CONSIDERED HAZARDOUS WASTE UNDER TITLE 40, CFR PART 261 (HAZARDOUS WASTES UNDER THE CONSERVATION RECOVERY ACT), REFERENCE SECTIONS 261.31, .32, .33(E) AND .33(F). THEY DO NOT HAVE THE CHARACTERISTICS OF A HAZARDOUS MATERIAL AS DEFINED UNDER SECTIONS 261.21, .22, .23, AND .24.

SECTION 7: HANDLING AND STORAGE

SPECIAL PRECAUTIONS

DO NOT USE PRESSURE TO EMPTY CONTAINER OR EXPLOSION MAY RESULT. DO NOT STORE AT TEMPERATUERS ABOVE 120°F. ODOR IS NOT AN ADEQUATE WARNING OF POTENTIALLY HAZARDOUS CONCENTRATIONS IN AIR. RELEASE OF THESE GASES MAY CAUSE A FLAMMABLE ATMOSPHERE WITH EXPLOSION POTENTIAL. WHEN UTILIZING PRESSURIZED CONTAINERS FOLLOW STANDARD SAFETY PRACTICES FOR HANDLING AEROSOLS.

SECTION 8: EXPOSURE CONTROLS PERSONAL PROTECTION

RESPIRATORY PROTECTION	HEALTH STUDIES HAVE SHOWN HYDROCARBONS POSE POTENTIAL HUMAN HEALTH RISKS FOR SOME PEOPLE. AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS AND FUMES SHOULD BE MINIMIZED. WEAR NIOSH/MSHA APPROVED RESPIRATORS WHENEVER CONCENTRATION IN AIR MAY EXCEED LIMITS.
EYE PROTECTION	WEAR SAFETY GLASSES WITH SIDE SHIELDS OR CHEMICAL GOGGLES
SKIN PROTECTION	WEAR LONG SLEEVES AND CHEMICAL RESISTANT GLOVES-POLYFLUORINATED POLYETHYLENE HAS BEEN SUGGESTED.
OTHER CLOTHING	STANDARD WORK CLOTHING. WASH AND DRY CONTAMINATED CLOTHING BEFORE REUSE
OTHER EQUIPMENT	USE ADEQUATE LEVEL EXHAUST VENTILATION. WHERE CARBON MONOXIDE MAY BE GENERATED, SPECIAL VENTILATION MAY BE REQUIRED. LOCAL EXHAUST RECOMMENDED WHEN APPROPRIATE TO CONTROL EXPOSURE.

SECTION 9: PHYSICAL DATA

CHEMICAL NAME	POLYMER	APPEARANCE	CLEAR
CHEMICAL FAMILY	NA	COLOR	CLEAR
CHEMICAL FORMULA	NA	STATE	AEROSOL
MOLECULAR WEIGHT	NA	ODOR	SLIGHT
DOT INFORMATION	NA	рН	NA
VAPOR DENSITY	NA	MELTING POINT	NA
VAPOR PRESSURE	<75 PSI	BOILING POINT	NA
SOLUBILITY-WATER	INSOLUBLE	FREEZING POINT	NA
SOLUBILITY-OIL	NA	PERCENT VOLATILITY	NA
SOLUBILITY-ACETONI	NA	EVAPORATION RATE	NA

SECTION 10: STABILITY AND REACTIVITY

STABILITY	STABLE
INCOMPATIBILITY (MATERIALS TO AVOID)	MAY REACT WITH STRONG OXIDIZING AGENTS
HAZARDOUS COMBUSTION OR DECOMP PRODUCTS	DECOMPOSITION MAY PRODUCE CARBON MONOXIDE
CONDITIONS TO AVOID	DO NOT WELD, HEAT OR DRILL CONTAINER (CAN). RESIDUE MAY IGNITE WITH EXPLOSIVE VIOLENCE IF HEATED SUFFICIENTLY. SPILLS ON SURFACES MAY CAUSE A SLIPPERY SURFACE.



SAFETY DATA SHEET (SDS)

SHEET 4 OF 4

PRIME LINE PRODUCTS, INC. 26950 SAN BERNARDINO AVE. REDLANDS, CA 92374

PH: 909-887-8118 FX: 909-880-2906

Email: info@prime-line-products.com EMERGENCY #: 800-255-3924, 909-887-8118

1221 (323)	
PRODUCT NAME	RZ-50 AEROSOL SPRAY LUBRICANT
PRODUCT PART NO.	RZ 50
PRODUCT DESC.	PTFE POLYMER DRY FILM AEROSOL LUBRIC
PRODUCT CLASS	LUBRICANT
C.A.S. NUMBER	0
SDS NUMBER	RZ-50
SDS DATE	2/18/2015

SECTION 11: TOXICOLOGICAL INFORMATION ACUTE DATA N/A REPRODUCTIVE / NA TERATOLOGY DATA **SECTION 12: ECOLOGICAL INFORMATION** NA **SECTION 13: DISPOSAL CONDITIONS** PRODUCTS COVERED BY THIS SDS, IN THEIR ORIGINAL FORM, WHEN DISPOSED AS WASTE, ARE IGNITABLE HAZARDOUS WASTE, D001, ACCORDING TO FEDERAL RCRA REGULATIONS (40 CFR 261). EMPTY DEPRESSURIZED CONTAINERS CANNOT BE REUSED. CANS WHICH ARE PRESSURIZED OR CONTAIN **PROCEDURES** LIQUID MUST BE DISPOSED IN A PERMITTED WASTE MANAGEMENT FACILITY. DISPOSAL MUST BE IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS. INCINERATION EQUIPMENT SHOULD BE CAPABLE OF HANDLING LARGE VOLUMES OF DENSE BLACK SMOKE AND WITHSTAND THE CORROSIVE EFFECTS OF ACID CASES. **SECTION 14: TRANSPORTATION INFORMATION** DOT Finished packaged product transported by ground (DOT): UN1950, Aerosol, Class 2.2, Ltd. Qty **CLASSIFICATION GHS LABELS** CATEGORY 1, DANGER, EXTREMELY FLAMMABLE AEROSOL, LTD. QTY

SECTION 16: OTHER INFORMATION

WORKPI ACE

CLASSIFICATION

SECTION 15: REGULATORY INFORMATION

THE INFORMATION PRESENTED IN THE SAFETY DATA SHEET IS BASED ON DATA BELIEVED TO BE ACCURATE AS OF THE DATE THIS SAFETY DATA SHEET WAS PREPARED. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. NO RESPONSIBILITY IS ASSUMED FOR ANY DAMAGE OR INJURY RESULTING FROM ABNORMAL USE OR FROM ANY FAILURE TO ADHERE TO RECOMMENDED PRACTICES. THE INFORMATION PROVIDED ABOVE AND THE PRODUCT, ARE FURNISHED ON THE CONDITION THAT THE PERSON RECEIVING THEM SHALL MAKE THEIR OWN DETERMINATION AS TO THE SUITABILITY OF THE PRODUCT FOR

NOT ESTABLISHED

THEIR PARTICULAR PURPOSE AND ON THE CONDITION THAT THEY ASSUME THE RISK OF THEIR USE.						
	_					