Page: 1
Printed: 01/26/2016
Revision: 07/21/2015

Supersedes Revision: 04/13/2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Klean Strip Easy Liquid Sander

Company Name: W. M. Barr Phone Number:

2105 Channel Avenue (901)775-0100

Memphis, TN 38113

Web site address: www.wmbarr.com

Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346 **Information:** W.M. Barr Customer Service (800)398-3892

Intended Use: Paint Adhesion Product

Product Code: QWN285

Additional Information This product is regulated by the United States Consumer Product Safety Commission

and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to

using the product.

2. HAZARDS IDENTIFICATION

Serious Eye Damage/Eye Irritation, Category 2
Specific Target Organ Toxicity (repeated exposure), Category 2





GHS Signal Word: Warning

GHS Hazard Phrases: H319: Causes serious eye irritation.

H373: May cause damage to {respiratory system} through prolonged or repeated

exposure.

GHS Precaution Phrases: P260: Do not breathe {dust/vapors/spray}.

P264: Wash {hands} thoroughly after handling.

P280: Wear {protective gloves}.

GHS Response Phrases: P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P314: Get medical attention/advice if you feel unwell.

P337+313: If eye irritation persists, get medical advice/attention.

GHS Storage and Disposal

Phrases:

P501: Dispose of contents/container according to local, state and federal regulations.

Hazard Rating System:





HMIS:

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

Page: 2
Printed: 01/26/2016
Revision: 07/21/2015

Supersedes Revision: 04/13/2015

Potential Health Effects (Acute and Chronic):

EYES: Can cause eye irritation.

SKIN: Can cause skin irritation.

INHALATION: May cause irritation of the respiratory tract, experienced as nasal

discomfort, possibly with chest pain and coughing.

INGESTION: Moderately toxic. May cause stomach or intestinal upset or discomfort

(nausea, vomiting, diarrhea).

This product contains crystalline silica in the form of quartz. In respirable form, chronic overexposure can cause lung disease and silicosis. The silica in this product is not in respirable form. The silica is encapsulated, which should present no health hazard due to inhalation exposure.

Medical Conditions Generally None known.

Aggravated By Exposure:

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS#	Hazardous Components (Chemical Name)	Concentration
112-34-5	Diethylene glycol monobutyl ether {2-(2-Butoxyethoxy)ethanol {(a glycol ether)}	5.0 -10.0 %
14808-60-7	Quartz {Silica-crystalline; Cistobalite; Tridymite}	3.0 -7.0 %
627-93-0	Dimethyl adipate	3.0 -7.0 %
1119-40-0	Dimethyl glutarate	2.0 -5.0 %
9036-19-5	Octylphenoxypolyethoxyethanol	1.0 -3.0 %

Additional Chemical

Specific percentage of composition is being withheld as a trade secret.

Information

4. FIRST AID MEASURES

Emergency and First Aid Procedures:

INHALATION:

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.

SKIN CONTACT:

Immediately wash with soap and water. Seek medical attention if irritation from contact persists.

EYE CONTACT:

Immediately flush with water, remove any contact lens, and continue flushing with water for at least 15 minutes. Get medical attention immediately.

INGESTION:

Do not induce vomiting, unless directed to by medical personnel. Call your poison control center, hospital, emergency room, or physician immediately for instructions. Do not give anything by mouth to an unconscious person.

Signs and Symptoms Of

Exposure:

See Potential Health Effects.

Note to Physician:

Treatment of overexposure should be directed at the control of symptoms and the clinical

Page: 3
Printed: 01/26/2016
Revision: 07/21/2015

Supersedes Revision: 04/13/2015

condition of the patient.

5. FIRE FIGHTING MEASURES

Flash Pt: No data.

Explosive Limits: LEL: No data. UEL: No data.

Autoignition Pt: No data.

Suitable Extinguishing Media: Non-combustible liquid - use extinguishing media for underlying cause of fire.

Unsuitable Extinguishing

None known.

Media:

Fire Fighting Instructions: If involved in a fire, wear self-contained breathing apparatus pressure-demand,

MSHA/NIOSH approved or equivalent) and full protective gear.

Flammable Properties and

Hazards:

No data available.

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Isolate the immediate area. Prevent unauthorized entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to compatible containers. For large spills, dike ahead of the spill.

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all waste regulations. Do not reuse this container.

Avoid contact with eyes, skin, and mucous membranes. Do not take internally.

Precautions To Be Taken in Storing:

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
112-34-5	Diethylene glycol monobutyl ether {2-(2-Butoxyethoxy)ethanol {(a glycol ether)}	No data.	No data.	No data.
14808-60-7	Quartz {Silica-crystalline; Cistobalite; Tridymite}	PEL: 8825 ppm/(%SiO2+5)	TLV: 0.05 mg/m3 (R)	No data.
627-93-0	Dimethyl adipate	No data.	No data.	No data.
1119-40-0	Dimethyl glutarate	No data.	No data.	No data.
9036-19-5	Octylphenoxypolyethoxyethanol	No data.	No data.	No data.

Page: 4 Printed: 01/26/2016 Revision: 07/21/2015

Supersedes Revision: 04/13/2015

Respiratory Equipment

(Specify Type):

For consumer use, use only with adequate ventilation. If strong odor is noticed or you experience slight dizziness - STOP - ventilation is inadequate. Leave area immediately.

For OSHA controlled workplace and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLVs. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirators for organic vapors.

A dust mask does not provide protection against vapors.

Eye Protection: Wear chemical splash goggles to safeguard against potential eye contact, irritation, or

For consumer use and when used as directed, usually none is required. People with **Protective Gloves:**

sensitive skin should wear chemical resistant gloves, such as nitrile or latex rubber

gloves.

Other Protective Clothing: Various application methods can dictate use of additional protective safety equipment,

> such as impermeable aprons, etc., to minimize exposure. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such

as gloves or shoes.

Engineering Controls (Ventilation etc.):

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering - STOP - ventilation is not adequate. Leave area immediately and move to

fresh air.

Work/Hygienic/Maintenance

Practices:

Wash hands thoroughly after use and before eating, drinking, or smoking.

Do not eat, drink, or smoke in the work area.

Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

[] Gas [X]Liquid [] Solid **Physical States:**

milky emulsion Appearance and Odor:

No data. **Melting Point:** > 212.00 F **Boiling Point:** No data. Autoignition Pt: Flash Pt: No data.

LEL: No data. UEL: No data. **Explosive Limits:**

Specific Gravity (Water = 1): No data. 8.6 LB/GL Density: Vapor Pressure (vs. Air or No data.

mm Hg):

Vapor Density (vs. Air = 1): > 1 **Evaporation Rate:** < 1

Solubility in Water: No data.

Page: 5
Printed: 01/26/2016
Revision: 07/21/2015

Supersedes Revision: 04/13/2015

Percent Volatile: 92.8 % by weight.

10. STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]

Conditions To Avoid - No data available.

Instability:

Incompatibility - Materials To Incompatible with strong oxidizers, alkalies, and acids.

Avoid:

Hazardous Decomposition or Decomposition may produce carbon monoxide and carbon dioxide.

Byproducts:

Possibility of Hazardous

Will occur [] Will not occur [X]

Reactions:

Conditions To Avoid -

No data available.

Hazardous Reactions:

11. TOXICOLOGICAL INFORMATION

Toxicological Information: This product has not been tested as a whole. Refer to section 2 for acute and chronic

effects.

CAS# 112-34-5:

Carcinogenicity/Other Information:

Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe.

Result:

Behavioral: Anticonvulsant.

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave.,

Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS# 14808-60-7:

Tumorigenic Effects:, TCLo, Inhalation, Rat, 50.00 MG/M3, 6 W.

Result:

Tumorigenic: Carcinogenic by RTECS criteria.

Liver: Tumors.

- Environmental Research., Academic Press, Inc., 1 E. First St., Duluth, MN 55802,

Vol/p/yr: 40,499, 1986

CAS# 9036-19-5:

Standard Draize Test, Eyes, Species: Rabbit, 1.000 %, Severe.

Result:

Lungs, Thorax, or Respiration: Changes in pulmonary vascular resistance.

Lungs, Thorax, or Respiration:Respiratory depression.

- Journal of the American Pharmaceutical Association, Scientific Edition., For publisher

information, see JPMSAE, Washington, DC, Vol/p/yr: 38,428, 1949

IARC 1 - Carcinogenic to humans

ACGIH A2 - Suspected Human Carcinogen

CAS # Hazardous Components (Chemical Name) NTP IARC ACGIH OSHA

Page: 6
Printed: 01/26/2016
Revision: 07/21/2015

Supersedes Revision: 04/13/2015

112-34-5	Diethylene glycol monobutyl ether {2-(2-Butoxyethoxy)ethanol {(a glycol ether)}	n.a.	n.a.	n.a.	n.a.
14808-60-7	Quartz {Silica-crystalline; Cistobalite; Tridymite}	Known	1	A2	n.a.
627-93-0	Dimethyl adipate	n.a.	n.a.	n.a.	n.a.
1119-40-0	Dimethyl glutarate	n.a.	n.a.	n.a.	n.a.
9036-19-5	Octylphenoxypolyethoxyethanol	n.a.	n.a.	n.a.	n.a.

12. ECOLOGICAL INFORMATION

General Ecological

Information:

No information available for this product as a whole.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with local, state, and federal laws.

Do not place material in general trash.

Do not allow material to enter bodies of water or sewers.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not regulated by D.O.T.

DOT Hazard Class: UN/NA Number:

Additional Transport

Information:

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
112-34-5	Diethylene glycol monobutyl ether {2-(2-Butoxyethoxy)ethanol {(a glycol ether)}	No	No	Yes-Cat. N230
14808-60-7	Quartz {Silica-crystalline; Cistobalite; Tridymite}	No	No	No
627-93-0	Dimethyl adipate	No	No	No
1119-40-0	Dimethyl glutarate	No	No	No
9036-19-5	Octylphenoxypolyethoxyethanol	No	No	No
This material meets the EPA [X] Yes [] No Acute (immediate) Health Hazard				

This material meets the EPA [X] Yes [] No Acute (immediate) Health Hazard
'Hazard Categories' defined [] Yes [X] No Chronic (delayed) Health Hazard
for SARA Title III Sections [] Yes [X] No Fire Hazard
311/312 as indicated: [] Yes [X] No Reactive Hazard

CAS#	Hazardous Components (Chemical Name)	Other US EPA or State Lists
112-34-5	Diethylene glycol monobutyl ether	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes -
	{2-(2-Butoxyethoxy)ethanol {(a glycol ether)}	Inventory, 4 Test; CA PROP.65: No
14808-60-7	Quartz {Silica-crystalline; Cistobalite; Tridymite}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -
		Inventory; CA PROP.65: No
627-93-0	Dimethyl adipate	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -
		Inventory, 12(b); CA PROP.65: No
1119-40-0	Dimethyl glutarate	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -

Page: 7
Printed: 01/26/2016
Revision: 07/21/2015

Supersedes Revision: 04/13/2015

Inventory, 12(b); CA PROP.65: No

CAA HAP, ODC: No; CWA NPDES: No; TSCA: Yes -

Inventory, 8A PAIR; CA PROP.65: No

16. OTHER INFORMATION

Revision Date: 07/21/2015

Preparer Name: W.M. Barr EHS Dept (901)775-0100

Additional Information About No data available.

Octylphenoxypolyethoxyethanol

This Product:

9036-19-5

Company Policy or

Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.