Material Name: Henry Easy Release Adhesive Remover

# \* \* \* Section 1 - Chemical Product and Company Identification \* \* \*

#### **Manufacturer Information**

The W.W. Henry Company 400 Ardex Park Drive Aliquippa, PA 15001 Phone: 724-203-8499

Emergency # CHEM-TEL 800-255-3924 1-813-248-0585 (Call collect)

MSDS ID: WWHC-003

## \* \* \* Section 2 - Hazards Identification \* \* \*

#### **Emergency Overview**

DANGER! Corrosive. Causes skin and eye burns. Toxic. Harmful if inhaled, swallowed or absorbed through the skin. Contains components which may be absorbed through the skin. May cause severe irritation to the respiratory tract if vapors are inhaled.

#### **Hazard Statements**

Do NOT get into eyes, on skin or on clothing. Do NOT breathe vapor. Do NOT swallow. Wash thoroughly after handling. Clean contaminated clothing before reuse. Keep container tightly closed. Use only with adequate ventilation. Keep out of the reach of children.

### **Potential Health Effects: Eyes**

Causes burns if in contact with the eyes. May cause permanent eye damage if not treated promptly.

### Potential Health Effects: Skin

Causes burns if in contact with the skin. Harmful if absorbed through the skin in significant amounts. Contains components for which skin absorption is possible.

### **Potential Health Effects: Ingestion**

Harmful if swallowed. May cause burns to the mouth, throat and digestive tract.

#### Potential Health Effects: Inhalation

Vapors are harmful if inhaled. May cause severe irritation to the respiratory system producing coughing and difficulty breathing. May cause drowsiness, dizziness, or loss of coordination if inhaled in large amounts.

**HMIS Ratings: Health:** 3 **Fire:** 0 **Reactivity:** 0 **Pers. Prot.:** safety glasses with side shields and gloves Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

# \* \* \* Section 3 - Composition / Information on Ingredients \* \* \*

CAS#	Component	Percent
141-43-5	Ethanolamine	7-13
111-76-2	2-Butoxyethanol	7-13

#### Component Information/Information on Non-Hazardous Components

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication). This product is a controlled product under the criteria specified in the Canadian Workplace Hazardous Materials Information System (WHMIS).

Page 1 of 8 Issue Date: 07/16/13 Revision: 1.0000 Print Date: 7/16/2013

MSDS ID: WWHC-003

#### Material Name: Henry Easy Release Adhesive Remover

## \* \* \* Section 4 - First Aid Measures \* \* \*

## First Aid: Eyes

Immediately flush eyes with large amounts of water, including under the eyelids, for 15-30 minutes. Remove contact lenses if present and easy to do. Obtain immediate medical attention.

#### First Aid: Skin

In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Wash with mild soap if needed to completely remove material. Obtain immediate medical attention.

## First Aid: Ingestion

Obtain immediate medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.

### First Aid: Inhalation

If inhaled, immediately remove the affected person to fresh air. If not breathing, have qualified personnel give artificial respiration and seek medical attention immediately.

## \* \* \* Section 5 - Fire Fighting Measures \* \* \*

#### **General Fire Hazards**

See Section 9 for Flammability Properties.

Material is not flammable.

#### **Hazardous Combustion Products**

Under conditions of fire, material may decompose and emit oxides of nitrogen, carbon monoxide, carbon dioxide, and/or low molecular weight hydrocarbons.

#### **Extinguishing Media**

Use extinguishing media appropriate for surrounding materials.

## Fire Fighting Equipment/Instructions

Firefighters should wear full-face, self contained breathing apparatus and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

### NFPA Ratings: Health: 3 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

## \* \* \* Section 6 - Accidental Release Measures \* \* \*

#### **Personal Precautions**

Do NOT get into eyes, on skin or on clothing. Do NOT breathe vapor. Do NOT swallow. Wash thoroughly after handling. Clean contaminated clothing before reuse. Keep container tightly closed. Use only with adequate ventilation.

#### **Containment Procedures**

Wear appropriate personal protective equipment to prevent contact with material during clean up procedure, including impervious gloves and safety glasses. Contain spill with inert material. Block any potential routes to water systems.

#### **Environmental Precautions**

Prevent discharge into sewers or waterways.

Page 2 of 8 Issue Date: 07/16/13 Revision: 1.0000 Print Date: 7/16/2013

Material Name: Henry Easy Release Adhesive Remover

## **Clean-Up Procedures**

Ventilate the area. If spill is large, be prepared to isolate the hazard area. Deny access to persons who are not involved in the cleanup and/or who have not been properly trained in spill management of hazardous liquids. Absorb spill with inert material. Carefully place material into appropriate container for disposal. Rinse area with clean, cold water and then dry.

MSDS ID: WWHC-003

#### **Evacuation Procedures**

Isolate area. Keep unnecessary personnel away.

### Special Procedures

Material is corrosive; avoid contact during clean up. Spilled material may be slippery.

\* \* \* Section 7 - Handling and Storage \* \* \*

## **Handling Procedures**

Observe good hygiene standards when handling this material. Do NOT get into eyes, on skin or on clothing. Do NOT breathe vapor. Do NOT swallow. Wash thoroughly after handling. Clean contaminated clothing before reuse. Keep container tightly closed. Use only with adequate ventilation.

## Storage Procedures

Store in a cool, dry, well-ventilated area. Do not store in open, unlabeled or mislabeled containers. Keep container tightly closed when not in use. Protect from freezing.

\* \* \* Section 8 - Exposure Controls / Personal Protection \* \* \*

### **Component Exposure Limits**

Consult local authorities for acceptable exposure limits.

### Ethanolamine (141-43-5)

ACGIH: 3 ppm TWA

6 ppm STEL

OSHA: 3 ppm TWA; 8 mg/m3 TWA

6 ppm STEL; 15 mg/m3 STEL

NIOSH: 3 ppm TWA; 8 mg/m3 TWA

6 ppm STEL; 15 mg/m3 STEL

Alberta: 3 ppm TWA; 7.5 mg/m3 TWA 6 ppm STEL; 15 mg/m3 STEL

British Columbia: 3 ppm TWA

6 ppm STEL

Manitoba: 3 ppm TWA

6 ppm STEL

New Brunswick: 3 ppm TWA; 7.5 mg/m3 TWA

6 ppm STEL; 15 mg/m3 STEL

NW Territories: 3 ppm TWA; 7.5 mg/m3 TWA 6 ppm STEL; 15 mg/m3 STEL

3 ppm TWA

6 ppm STEL

Nunavut: 3 ppm TWA; 7.5 mg/m3 TWA

6 ppm STEL; 15 mg/m3 STEL

Ontario: 3 ppm TWAEV; 7.5 mg/m3 TWAEV 6 ppm STEV; 15 mg/m3 STEV

Quebec: 3 ppm TWAEV; 7.5 mg/m3 TWAEV

6 ppm STEV; 15 mg/m3 STEV

Saskatchewan: 3 ppm TWA

Nova Scotia:

6 ppm STEL

Yukon: 3 ppm TWA; 6 mg/m3 TWA

6 ppm STEL; 12 mg/m3 STEL

Page 3 of 8 Issue Date: 07/16/13 Revision: 1.0000 Print Date: 7/16/2013

Material Name: Henry Easy Release Adhesive Remover MSDS ID: WWHC-003

### 2-Butoxyethanol (111-76-2)

ACGIH: 20 ppm TWA

OSHA: 25 ppm TWA; 120 mg/m3 TWA
Prevent or reduce skin absorption

NIOSH: 5 ppm TWA; 24 mg/m3 TWA

Potential for dermal absorption

Alberta: 20 ppm TWA; 97 mg/m3 TWA

British Columbia: 20 ppm TWA Manitoba: 20 ppm TWA

New Brunswick: 25 ppm TWA; 121 mg/m3 TWA NW Territories: 25 ppm TWA; 120 mg/m3 TWA

75 ppm STEL; 360 mg/m3 STEL

Nova Scotia: 20 ppm TWA

Nunavut: 25 ppm TWA; 120 mg/m3 TWA

75 ppm STEL; 360 mg/m3 STEL

Ontario: 20 ppm TWAEV

Quebec: 20 ppm TWAEV; 97 mg/m3 TWAEV

Saskatchewan: 20 ppm TWA

30 ppm STEL

Yukon: 50 ppm TWA; 240 mg/m3 TWA

150 ppm STEL; 720 mg/m3 STEL

## **Engineering Controls**

Ventilation should effectively remove and prevent buildup of any vapor or mist generated from the handling of this product.

### PERSONAL PROTECTIVE EQUIPMENT

## Personal Protective Equipment: Eyes/Face

Chemical splash goggles or safety glasses with side shields are recommended.

### Personal Protective Equipment: Skin

Wear impervious gloves. Materials such as rubber or latex are recommended.

#### Personal Protective Equipment: Respiratory

Under normal conditions of use, respiratory protection should not be necessary.

#### **Personal Protective Equipment: General**

Eye wash fountains and emergency showers are required in the workplace when handling corrosive substances. Use good industrial hygiene practices when handling this material.

# \* \* \* Section 9 - Physical & Chemical Properties \* \* \*

Appearance: Solution Color: Pale amber
Odor: Not available Physical State: Liquid

Vaner Program: Not available

PH: 12.1 Vapor Pressure: Not available Vapor Density: Not available Boiling Point: >212° F (>100° C)

Melting Point:Not availableSolubility (H2O):MiscibleSpecific Gravity:1.05Flash Point:>230° F (110° C)

Flash Point Method: Setaflash Closed Tester LFL: Not available Auto Ignition: Not available UFL: Not available

Percent Volatile: > 95 % VOC Content: 4.4% per CARB, after dilution

# \* \* \* Section 10 - Chemical Stability & Reactivity Information \* \* \*

#### Chemical Stability

Stable under normal conditions.

Page 4 of 8 Issue Date: 07/16/13 Revision: 1.0000 Print Date: 7/16/2013

Material Name: Henry Easy Release Adhesive Remover

#### **Conditions to Avoid**

None known.

### Incompatibility

Avoid contact with acids and strong oxidizing agents.

#### **Hazardous Decomposition**

Under conditions of fire, material may decompose and emit oxides of nitrogen, carbon monoxide, carbon dioxide, and/or low molecular weight hydrocarbons.

MSDS ID: WWHC-003

### **Possibility of Hazardous Reactions**

Hazardous polymerization will not occur.

## \* \* \* Section 11 - Toxicological Information \* \* \*

#### **Acute Dose Effects**

#### A: General Product Information

Harmful if inhaled, swallowed or absorbed through the skin. Contains components which may be absorbed through the skin in harmful amounts.

#### B: Component Analysis - LD50/LC50

#### **Ethanolamine (141-43-5)**

Oral LD50 Rat: 1720 mg/kg; Dermal LD50 Rabbit: 1 mL/kg; Dermal LD50 Rabbit: 1025 mg/kg

#### 2-Butoxyethanol (111-76-2)

Inhalation LC50 Rat: 2.21 mg/L/4H; Inhalation LC50 Rat: 450 ppm/4H; Oral LD50 Rat: 470 mg/kg; Dermal LD50 Rat: 2270 mg/kg; Dermal LD50 Rabbit: 220 mg/kg

## **Repeated Dose Effects**

Contains components which may be absorbed through the skin in harmful amounts, especially after repeated or prolonged exposure.

#### Corrosivity

Causes skin and eye burns. May cause permanent eye damage.

#### Carcinogenicity

#### A: General Product Information

No information is available for the product.

#### **B: Component Carcinogenicity**

### 2-Butoxyethanol (111-76-2)

ACGIH: A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans

IARC: Monograph 88 [2006] (Group 3 (not classifiable))

# \* \* \* Section 12 - Ecological Information \* \* \*

### **Ecotoxicity**

#### A: General Product Information

No information is available for the product.

#### B: Component Analysis - Ecotoxicity - Aquatic Toxicity

Ethanolamine (141-43-5)

**Test & Species**96 Hr LC50 Pimephales promelas

227 mg/L

[flow-through]

Page 5 of 8 Issue Date: 07/16/13 Revision: 1.0000 Print Date: 7/16/2013

MSDS ID: WWHC-003

#### Material Name: Henry Easy Release Adhesive Remover

96 Hr LC50 Brachydanio rerio 3684 mg/L [static]

72 Hr EC50 Scenedesmus subspicatus 15 mg/L 48 Hr EC50 Daphnia magna 65 mg/L

2-Butoxyethanol (111-76-2)

Test & Species Conditions

 96 Hr LC50 Lepomis macrochirus
 2950 mg/L

 24 Hr EC50 water flea
 1720 mg/L

 24 Hr LC50 Daphnia magna
 1698-1940 mg/L

#### **Bioaccumulation & Accumulation**

Not expected to bioaccumulate.

### **Mobility in Environmental Media**

Material is completely miscible in water.

#### **Other Adverse Effects**

Material is highly alkaline and should not be discharged into sewers or waterways.

## \* \* \* Section 13 - Disposal Considerations \* \* \*

## **US EPA Waste Number & Descriptions**

#### A: General Product Information

Material, if discarded, is not expected to be a characteristic hazardous waste under RCRA. You must test your waste using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes.

#### **B: Component Waste Numbers**

No EPA Waste Numbers are applicable for this product's components.

#### **Disposal Instructions**

Waste must be handled in accordance with all federal, state, provincial, and local regulations. In case of large spills, follow all facility Emergency Response Procedures. Do not allow this material to into sewers/water supplies. Do not reuse container. Dispose of container and any unused contents in accordance with Federal, State, Provincial and Local Waste Regulations.

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

# \* \* \* Section 14 - Transportation Information \* \* \*

#### **US DOT Information**

UN Number: UN 2491

**Shipping Name:** Ethanolamine solutions.

Hazard Class: 8
Packing Group: III

**TDG Information** 

UN Number: UN 2491

**Shipping Name:** Ethanolamine solutions.

Hazard Class: 8
Packing Group: III

Page 6 of 8 Issue Date: 07/16/13 Revision: 1.0000 Print Date: 7/16/2013

Material Name: Henry Easy Release Adhesive Remover

# \* \* \* Section 15 - Regulatory Information \* \* \*

MSDS ID: WWHC-003

## **US Federal Regulations**

### A: Component Analysis

None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

Acute Health: Yes Chronic Health: No Fire: No Pressure: No Reactive: No

#### **B: Component Marine Pollutants**

No information is available.

## **State Regulations**

### **Component Analysis - State**

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Ethanolamine	141-43-5	Yes	Yes	Yes	Yes	Yes	Yes
2-Butoxyethanol	111-76-2	Yes	Yes	Yes	Yes	Yes	Yes

## **Component Analysis - WHMIS IDL**

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS#	Minimum Concentration		
Ethanolamine	141-43-5	1 %		
2-Butoxyethanol	111-76-2	1 %		

### WHMIS Classification: D1A, E

#### **Additional Regulatory Information**

#### **Component Analysis – Inventory**

Component	CAS#	TSCA	CAN	EEC
Ethanolamine	141-43-5	Yes	DSL	EINECS
2-Butoxyethanol	111-76-2	Yes	DSL	EINECS

# \* \* \* Section 16 - Other Information \* \* \*

#### Other Information

Additional Safety Information for Consumers:

Keep locked up and out of the reach of children.

Wear suitable protective clothing, gloves and eye/face protection.

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Page 7 of 8 Issue Date: 07/16/13 Revision: 1.0000 Print Date: 7/16/2013

Material Name: Henry Easy Release Adhesive Remover MSDS ID: WWHC-003

## Key/Legend

ACGIH = American Conference of Governmental Industrial Hygienists; CARB = California Air Resources Board; CAS = Chemical Abstracts Service; CERCLA = Comprehensive Environmental Response, Compensation, and Liability Act; CFR = Code of Federal Regulations; CPR = Controlled Products Regulations; DOT = Department of Transportation; DSL = Domestic Substances List; EINECS = European Inventory of Existing Commercial Chemical Substances; EPA = Environmental Protection Agency; IARC = International Agency for Research on Cancer; IATA = International Air Transport Association; mg/Kg = milligrams per Kilogram; mg/L = milligrams per Liter; mg/m3 = milligrams per Cubic Meter; MSHA = Mine Safety and Health Administration; NA = Not Applicable or Not Available; NIOSH = National Institute for Occupational Safety and Health; NJTSR = New Jersey Trade Secret Registry; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; SARA = Superfund Amendments and Reauthorization Act; TDG = Transport Dangerous Goods; TSCA = Toxic Substances Control Act; WHMIS = Workplace Hazardous Materials Information System.

End of Sheet WWHC-003

Page 8 of 8 Issue Date: 07/16/13 Revision: 1.0000 Print Date: 7/16/2013