

SAFETY DATA SHEET

1. Identification

Product identifier Oatey Plumber's Putty

Other means of identification

Product code 1705E

Synonyms Part Numbers: 31166, 31167, 31170, 31174, 48003, 48004

Recommended use Plumbing Mastic

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards.

Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer Distributor

Company Name Oatey Co. Oatey Canada Supply Chain Services Co.

Address 4700 West 160th St. 145 Walker Drive

Cleveland, OH 44135 Brampton, ON L6T 5P5, Canada

Telephone 216-267-7100 E-mail info@oatey.com

Transport Emergency Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)

Emergency First Aid 1-877-740-5015

Contact person MSDS Coordinator

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Health hazards not otherwise classified Category 1

Environmental hazards Not classified.

Label elements



Signal word Danger

Hazard statement Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Limestone	1317-65-3	60-90
Distillates, Petroleum, Hydrotreated Heavy Naphthenic	64742-52-5	5-30

Oatey Plumber's Putty SDS Canada

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.

Most important Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

symptoms/effects, acute and Coughing.

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

and precautions for firefighters
Fire fighting

Move containers from fire area if you can do so without risk.

equipment/instructions
Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Following product recovery, flush area with water.

For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form
Distillates, Petroleum, Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Quartz (Silica Crystalline) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

Oatey Plumber's Putty SDS Canada

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Туре	Value	Form
Distillates, Petroleum, Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Limestone (CAS 1317-65-3)	TWA	10 mg/m3	
Quartz (Silica Crystalline) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
Limestone (CAS 1317-65-3)	STEL	20 mg/m3	Total dust.
	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Quartz (Silica Crystalline) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value	Form
Distillates, Petroleum, Hydrotreated Heavy	TWA	5 mg/m3	Inhalable fraction.
Naphthenic (CAS 64742-52-5)			
Quartz (Silica Crystalline) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	Form
Distillates, Petroleum, Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Quartz (Silica Crystalline) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Туре	Value	Form
Distillates, Petroleum, Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Limestone (CAS 1317-65-3)	TWA	10 mg/m3	Total dust.
Quartz (Silica Crystalline) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica

should be monitored and controlled. Occupational Exposure Limits are not relevant to the current

physical form of the product.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Oatey Plumber's Putty SDS Canada

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

Use a particulate filter respirator for particulate concentrations exceeding the Occupational Respiratory protection

Exposure Limit.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Solid. **Physical state Form** Putty. Color Off-white. Slight. Odor

Not available. **Odor threshold** Not applicable Not available. Melting point/freezing point Initial boiling point and boiling Not determined

range

> 212.0 °F (> 100.0 °C) Flash point

Not available. **Evaporation rate** Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits Not available.

Flammability limit - lower

(%)

Flammability limit - upper

Not available.

Not available. **Explosive limit - lower (%)** Not available. Explosive limit - upper (%) Not available. Vapor pressure Not available. Vapor density

Relative density 1.87

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature Viscosity** > 500000 cP

Other information

Explosive properties Not explosive. Not oxidizing. **Oxidizing properties**

VOC (Weight %) 20 g/l

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. **Chemical stability**

Oatey Plumber's Putty SDS Canada

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Contact with incompatible materials.

Incompatible materials

Acids. Fluorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

No adverse effects due to skin contact are expected. Skin contact Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Coughing. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and

dermatitis.

Information on toxicological effects

Not expected to be acutely toxic. Acute toxicity

Skin corrosion/irritation Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

This product is not expected to cause skin sensitization.

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

Limestone (CAS 1317-65-3)

Irritant

Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

ACGIH Carcinogens

Distillates, Petroleum, Hydrotreated Heavy Naphthenic

A2 Suspected human carcinogen.

(CAS 64742-52-5)

A4 Not classifiable as a human carcinogen.

Quartz (Silica Crystalline) (CAS 14808-60-7)

A2 Suspected human carcinogen.

Canada - Alberta OELs: Carcinogen category

Quartz (Silica Crystalline) (CAS 14808-60-7) Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

MINERAL OIL, EXCLUDING METAL WORKING FLUIDS, Suspected human carcinogen.

POORLY AND MILDLY REFINED (CAS 64742-52-5)

MINERAL OIL, EXCLUDING METAL WORKING FLUIDS, Not classifiable as a human carcinogen.

PURE, HIGHLY AND SEVERELY REFINED, INHALABLE FRACTION (CAS 64742-52-5)

SILICA, CRYSTALLINE-.ALPHA.-QUARTZ, Suspected human carcinogen. RESPIRABLE FRACTION (CAS 14808-60-7)

Oatey Plumber's Putty SDS Canada

Canada - Quebec OELs: Carcinogen category

Quartz (Silica Crystalline) (CAS 14808-60-7) Suspected carcinogenic effect in humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (Silica Crystalline) (CAS 14808-60-7) 1 Carcinogenic to humans.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

Not classified.

single exposure

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS

contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Oatey Plumber's Putty

925325 Version #: 03 Revision date: 10-April-2018 Issue date: 10-December-2015 6/7

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or regionInventory nameOn inventory (yes/no)*CanadaDomestic Substances List (DSL)NoCanadaNon-Domestic Substances List (NDSL)YesUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

16. Other Information

Issue date10-December-2015Revision date24-May-2016

Version # 02

Disclaimer Oatey Co. cannot anticipate all conditions under which this information and its product, or the

products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

Oatey Plumber's Putty SDS Canada

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).