

SAFETY DATA SHEET

Version 6.3 Revision Date 01/15/2020 Print Date 02/20/2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 **Product identifiers**

Product name : 2-Propanol

Product Number : 34863 Brand **SIGALD**

Index-No. : 603-117-00-0 CAS-No. : 67-63-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company Sigma-Aldrich Inc.

> 3050 Spruce Street ST. LOUIS MO 63103 **UNITED STATES**

Telephone : +1 314 771-5765 : +1 800 325-5052 Fax

Emergency telephone number

Emergency Phone # : +1-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225

Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

SIGALD - 34863 Page 1 of 11



H336	May cause drowsiness or dizziness.
Precautionary statement(s)	
P210	Keep away from heat/sparks/open flames/hot surfaces. No
	smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ eye protection/ face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated
D204 - D240 - D242	clothing. Rinse skin with water/shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable
D205 - D254 - D220	for breathing. Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes.
	Remove contact lenses, if present and easy to do. Continue
P337 + P313	rinsing. If over irritation persists, Cet medical advise/ attention
	If eye irritation persists: Get medical advice/ attention.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 P403 + P235	Store in a well-ventilated place. Keep container tightly closed.
P405 + F255	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal
1 301	plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

May form explosive peroxides.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : sec-Propyl alcohol

Isopropyl alcohol Isopropanol

Component	Classification	Concentration
2-Propanol		
•	Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3; H225, H319, H336 Concentration limits: >= 20 %: STOT SE 3,	<= 100 %

SIGALD - 34863 Page 2 of 11



H336;

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Dry powder Dry sand

Unsuitable extinguishing media

Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.



SIGALD - 34863 Page 3 of 11

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Handle and store under inert gas. hygroscopic Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis	
2-Propanol	67-63-0	TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)	
	Remarks	Central Nervous System impairment Upper Respiratory Tract irritation Eye irritation Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen			

SIGALD - 34863 Page 4 of 11



STEL	400 ppm	USA. ACGIH Threshold Limit Values (TLV)	
Central Nervous System impairment Upper Respiratory Tract irritation Eye irritation Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen			
TWA	400 ppm 980 mg/m3	USA. NIOSH Recommended Exposure Limits	
ST	500 ppm 1,225 mg/m3	USA. NIOSH Recommended Exposure Limits	
TWA	400 ppm 980 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants	
The value in mg/m3 is approximate.			
PEL	400 ppm 980 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
STEL	500 ppm 1,225 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	

Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis	
2-Propanol	67-63-0	Acetone	40 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)	
	Remarks	End of shift at end of workweek				

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

SIGALD - 34863 Page 5 of 11



Break through time: 480 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.2 mm Break through time: 60 min

Material tested: Dermatril® P (KCL 743 / Aldrich Z677388, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail

sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Colour: colourless

b) Odour alcohol-like

c) Odour Threshold No data available

d) pH at 20 °C (68 °F)neutral

e) Melting point/range: -89.5 °C (-129.1 °F)

point/freezing point

f) Initial boiling point 82 °C 180 °F

and boiling range

g) Flash point 12.0 °C (53.6 °F) - closed cup

h) Evaporation rate 3.0

i) Flammability (solid, No data available

gas)

j) Upper/lower Upper explosion limit: 13.4 %(V) flammability or Lower explosion limit: 2 %(V)

SIGALD - 34863 Page 6 of 11

explosive limits

k) Vapour pressure 43 hPa at 20 °C (68 °F)

I) Vapour density 2.07

m) Relative density 0.785 g/mL at 25 °C (77 °F)

n) Water solubility soluble

o) Partition coefficient: log Pow: 0.05 - Bioaccumulation is not expected.

n-octanol/water

p) Auto-ignition 425.0 °C (797.0 °F)

temperature

g) Decomposition Distillable in an undecomposed state at normal pressure.

temperature

r) Viscosity No data availables) Explosive properties No data availablet) Oxidizing properties No data available

9.2 Other safety information

Minimum ignition 0.65 mJ

energy

Conductivity $< 0.1 \mu S/cm$

Surface tension 20.8 mN/m at 25.0 °C (77.0 °F)

Relative vapour

density

2.07

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Reacts with air to form peroxides.

Test for peroxide formation before distillation or evaporation. Test for peroxide formation or discard after 1 year.

Stable under recommended storage conditions.

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air. Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Oxidizing agents, Acid anhydrides, Aluminium, Halogenated compounds, Acids

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available

In the event of fire: see section 5

SIGALD - 34863 Page 7 of 11

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 5,840 mg/kg (OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 37.5 mg/l

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - 12,800 mg/kg

Remarks: (RTECS) No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h (OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Eye irritation

(OECD Test Guideline 405)

(Regulation (EC) No 1272/2008, Annex VI)

Respiratory or skin sensitisation

Buehler Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

Ames test

Salmonella typhimurium

Result: negative

In vitro mammalian cell gene mutation test

Chinese hamster ovary cells

Result: negative

OECD Test Guideline 474

Mouse - male and female - Bone marrow

Result: negative

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation, Oral - May cause drowsiness or dizziness. - Central nervous system Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2) Acute inhalation toxicity - Central nervous system

SIGALD - 34863 Page 8 of 11

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: NT8050000

Central nervous system depression, prolonged or repeated exposure can cause:, Nausea, Headache, Vomiting, narcosis, Drowsiness, Overexposure may cause mild, reversible liver effects., Aspiration may lead to:, Lung oedema, Pneumonia

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

After absorption:

Headache, Dizziness, inebriation, Unconsciousness, narcosis

After uptake of large quantities:

Handle in accordance with good industrial hygiene and safety practice.

Kidney - Irregularities - Based on Human Evidence

Kidney - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish flow-through test LC50 - Pimephales promelas (fathead minnow) -

9,640 mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia and other aquatic

Remarks: (IUCLID)

invertebrates

Toxicity to algae

IC50 - Desmodesmus subspicatus (green algae) - > 1,000 mg/l - 72

EC50 - Daphnia magna (Water flea) - 13,299 mg/l - 48 h

Remarks: (IUCLID)

Toxicity to bacteria EC5 - Pseudomonas putida - 1,050 mg/l - 16 h

Remarks: (Lit.)

12.2 Persistence and degradability

aerobic - Exposure time 5 d Biodegradability

> Result: 53 % - Readily biodegradable. (Directive 67/548/EEC, Annex V, C.6)

Theoretical oxygen 2,400 mg/g demand Remarks: (Lit.)

Ratio BOD/ThBOD 49 %

Remarks: (IUCLID)

12.3 Bioaccumulative potential

No bioaccumulation is to be expected (log Pow \leq 4).

12.4 Mobility in soil

No data available

SIGALD - 34863 Page 9 of 11

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Contact a licensed professional waste disposal service to dispose of this material. Offer surplus and non-recyclable solutions to a licensed disposal company. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

DOT (US)

UN number: 1219 Class: 3 Packing group: II

Proper shipping name: Isopropanol

Reportable Quantity (RQ): Poison Inhalation Hazard: No

IMDG

UN number: 1219 Class: 3 Packing group: II EMS-No: F-E, S-D

Proper shipping name: ISOPROPANOL

IATA

UN number: 1219 Class: 3 Packing group: II

Proper shipping name: Isopropanol

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

2-Propanol CAS-No. Revision Date 2-Propanol 67-63-0 2007-03-01

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SIGALD - 34863 Page 10 of 11

CAS-No. 67-63-0 Revision Date 2007-03-01

SECTION 16: Other information

Further information

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.3 Revision Date: 01/15/2020 Print Date: 02/20/2020

SIGALD - 34863 Page 11 of 11

