Page: 1/8



Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 27, 2020

1 Identification

- · Product identifier
- · Trade name: Slime Tire Sealant
- · Product code: See section 16 for list of product codes.
- · Other means of identification:

Tire Sealant

Slime TPMS Sealant

- · Recommended use and restriction on use
- · Recommended use: Sealant
- · Restrictions on use: No relevant information available.
- Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

ITW Global Tire Repair, Inc.

125 Venture Drive, Suite 210, San Luis Obispo, CA 93401

Tel (805) 489-0490

· Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America)

+1 (813)248-0585 (International)

2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified as hazardous according to the Globally Harmonized System (GHS).

- · Label elements
- · GHS label elements Not regulated.
- · Hazard pictograms: Not regulated.
- · Signal word: Not regulated.
- · Hazard statements: Not regulated.
- Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Componer	nts:	
56-81-5	Glycerol	20-40%
9004-34-6	cellulose	<5%

Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

4 First-aid measures

- Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

(Cont'd. on page 2)

Page: 2/8



Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 27, 2020

Trade name: Slime Tire Sealant

(Cont'd. of page 1)

Immediately remove any clothing soiled by the product.

Do not pull solidified product away from the skin.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· Most important symptoms and effects, both acute and delayed:

Gastric or intestinal disorders

Slight irritant effect on skin and mucous membranes.

Slight irritant effect on eyes.

Indication of any immediate medical attention and special treatment needed: Treat symptomatically.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

- · For safety reasons unsuitable extinguishing agents: None.
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required.

Ensure adequate ventilation.

- **Environmental precautions** Avoid release to the environment.
- · Methods and material for containment and cleaning up

Allow to solidify. Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- ·Handling
- · Precautions for safe handling:

(Cont'd. on page 3)

Page: 3/8



Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 27, 2020

Trade name: Slime Tire Sealant

(Cont'd. of page 2)

Keep out of reach of children.

Open and handle receptacle with care.

Use only in well ventilated areas.

- Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from frost.

· Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components w	rith limit values that require monitoring at the workplace:		
56-81-5 Glycerol			
PEL (USA)	Long-term value: 15* 5** mg/m³ mist; *total dust **respirable fraction		
TLV (USA)	TLV withdrawn-insufficient data human occup. exp.		
EL (Canada)	Long-term value: 10* 3** mg/m³ *mist, total; **mist, respirable		
EV (Canada)	Long-term value: 10 mg/m³		
LMPE (Mexico)	Long-term value: 10 mg/m³		
9004-34-6 cellu	lose		
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction		
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction		
TLV (USA)	Long-term value: 10 mg/m³		
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust, **respirable fraction		
EV (Canada)	Long-term value: 10 mg/m³ paper fibre, total dust		
LMPE (Mexico)	Long-term value: 10 mg/m³		

Exposure controls

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Avoid breathing mist, vapors, or spray.

- Engineering controls: Provide adequate ventilation.
- Breathing equipment:

Not required under normal conditions of use.

(Cont'd. on page 4)



Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 27, 2020

Trade name: Slime Tire Sealant

(Cont'd. of page 3)

Use suitable respiratory protective device in case of insufficient ventilation. For spills, respiratory protection may be advisable.

Protection of hands:



Protective gloves

Material: Nitrile Thickness: ≥4 mil

Breakthrough time: 2 hours

· Eye protection:



Safety glasses

- · Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment

No relevant information available.

· Risk management measures No relevant information available.

Information on basic physical and chemical properties					
Appearance:	o				
Form:	Liquid				
Color:	Green				
Odor:	Characteristic				
Odor threshold:	Not determined.				
pH-value:	Not determined.				
Melting point/Melting range:	Not determined.				
Boiling point/Boiling range:	Not determined.				
Flash point:	Not determined.				
Flammability (solid, gaseous):	Not applicable.				
Auto-ignition temperature:	Not determined.				
Danger of explosion:	Product does not present an explosion hazard.				
Explosion limits					
Lower:	Not determined.				
Upper:	Not determined.				
Oxidizing properties:	Non-oxidizing.				
Vapor pressure:	Not determined.				
Density:					
Relative density:	Not determined.				
Vapor density:	Not determined.				
Evaporation rate:	Not determined.				

Page: 5/8



Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 27, 2020

Trade name: Slime Tire Sealant

(Cont'd. of page 4)

· Solubility in / Miscibility with

Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity

Dynamic: Not determined. **Kinematic:** Not determined.

• Other information No relevant information available.

10 Stability and reactivity

- · **Reactivity:** No relevant information available.
- · Chemical stability:
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- Possibility of hazardous reactions Reacts with strong acids and oxidizing agents.
- Conditions to avoid

Excessive heat.

Prevent from drying out.

- · Incompatible materials No relevant information available.
- · Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Slight irritant effect on skin and mucous membranes.
- · On the eye: Slight irritant effect on eyes.
- Sensitization: Based on available data, the classification criteria are not met.
- · IARC (International Agency for Research on Cancer):

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

Present in trace quantities.

14808-60-7 Quartz

| 1

NTP (National Toxicology Program):

14808-60-7 Quartz

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

Probable route(s) of exposure:

Ingestion.

Eye contact.

(Cont'd. on page 6)

Page: 6/8



Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 27, 2020

Trade name: Slime Tire Sealant

(Cont'd. of page 5)

Skin contact.

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available.
- Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- **Uncleaned packagings**
- · **Recommendation:** Disposal must be made according to official regulations.

UN-Number		
DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
UN proper shipping name DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
Transport hazard class(es)		
DOT, ADR/RID/ADN, IMDG, IATA Class	Not regulated.	
Packing group DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
Environmental hazards Marine pollutant:	No	
Special precautions for user	Not applicable.	

Page: 7/8



Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 27, 2020

Trade name: Slime Tire Sealant

(Cont'd. of page 6)

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

Present in trace quantities.

14808-60-7 Quartz

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

Present in trace quantities.

14808-60-7 Quartz

1

· Canadian Domestic Substances List (DSL):

All ingredients are listed or exempt.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Cont'd. on page 8)

Page: 8/8



Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 27, 2020

Trade name: Slime Tire Sealant

(Cont'd. of page 7)

· Product codes:

10006, 10007, 10008, 10009, 10010, 10010-60, 10011, 10011-35, 10012, 10016, 10016/60, 10017, 10019, 10020, 10022, 10022-M, 10023, 10023-M, 10024, 10024-M, 10030, 10031, 10033, 10040, 10041, 10042, 10043, 10047, 10048, 10141, 10143, 10144, 10047, 10054, 10082, 10088, 10093, 10094, 10099, 10104/60, 10105SL, 10113, 10123, 10124, 10125, 10129, 10136, 10142, 10149, 10163, 10164, 10167, 10169, 10170, 10171, 10178, 10184, 20282, 40002, 50001, 50009, 50024, 50036, 50040, 50046, 50047, 50050, 50054, 50056, 50057, 50058, 50063, 50107, 70004, 70005, 100027, 400011, 500362, 500472, 70004, PWR-005, SB-55G-AMI, SDS-500-02-2A, SDS-500/02-3A, SDS-500/30, SDS-500/30-IN, SDS-TIRE, SDSB TIRE, SDSB-1G-1/4PAL, SDSB-55G, SS-PDQ/06, SDS-500/06-IN, 100001, 100006, 100641, SDSB-1G/02, SDSB-1G/02-IN, SDSB-5G, SDSB-5G-IN, CRK0305-IN, CRK0305-MTD

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com