SAFETY DATA SHEET

1. Identification

Product identifier Water Extraction Carpet Cleaner

Other means of identification

F534022 Product code

Recommended use Concentrated Extraction Cleaner

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Franklin Cleaning Technology Company name

Address One Fuller Way

Great Bend, KS 67530

United States

Customer Service Telephone

E-mail Not available.

CHEMTREC (800) 424-9300 **Emergency phone number**

> Emergency (620) 792-1711 (800) 424-9300 24 hour Emergency

2. Hazard(s) identification

Not classified. **Physical hazards**

Health hazards Skin corrosion/irritation Category 2

> Serious eye damage/eye irritation Category 2

(800) 810-4829

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment,

Category 3

long-term hazard **OSHA** defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life. Harmful to aquatic life

with long lasting effects.

Precautionary statement

Prevention Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves. Wear

eye/face protection.

If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Response

Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see this label). If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical

advice/attention. Take off contaminated clothing and wash before reuse.

Store away from incompatible materials. Storage

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise

None known. classified (HNOC)

Supplemental information 13.7% of the mixture consists of component(s) of unknown acute hazards to the aquatic

environment. 13.7% of the mixture consists of component(s) of unknown long-term hazards to the

aquatic environment.

Material name: Water Extraction Carpet Cleaner 1414 Version #: 01 Issue date: 12-31-2014

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
BUTOXYETHANOL		111-76-2	3 - < 5
DIPROPYLENE GLYCOL MONOMETHYL ETHER		34590-94-8	1 - < 3
SODIUM SILICATE		1344-09-8	1 - < 3
POTASSIUM HYDROXIDE		1310-58-3	< 1
Other components below reportable le	vels		90 - 100

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

vision. Skin irritation. May cause redness and pain.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire-fighting equipment/instructions

Specific methods General fire hazards During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Provide adequate

ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene

practices. Avoid release to the environment. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type `	Value	
BUTOXYETHANOL (CAS 111-76-2)	PEL	240 mg/m3	
		50 ppm	
DIPROPYLENE GLYCOL	PEL	600 mg/m3	
MONOMETHYL ETHER			
(CAS 34590-94-8)		400	
		100 ppm	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	
BUTOXYETHANOL (CAS 111-76-2)	TWA	20 ppm	
DIPROPYLENE GLYCOL MONOMETHYL ETHER	STEL	150 ppm	
(CAS 34590-94-8)			
	TWA	100 ppm	
POTASSIUM HYDROXIDE (CAS 1310-58-3)	Ceiling	2 mg/m3	
US. NIOSH: Pocket Guide to Chemic	al Hazards		
Components	Туре	Value	
BUTOXYETHANOL (CAS 111-76-2)	TWA	24 mg/m3	
		5 ppm	
DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS 34590-94-8)	STEL	900 mg/m3	
(2.12.27333.37		150 ppm	
	TWA	600 mg/m3	
		100 ppm	
POTASSIUM HYDROXIDE (CAS 1310-58-3)	TWA	2 mg/m3	

Biological limit values

ACGIH Biological	Exposure Indices
0	\/-I

Components	Value	Determinant	Specimen	Sampling Time
BUTOXYETHANOL (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

BUTOXYETHANOL (CAS 111-76-2)

DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS Can be absorbed through the skin. 34590-94-8)

US - Minnesota Haz Subs: Skin designation applies

BUTOXYETHANOL (CAS 111-76-2) Skin designation applies.

US - Tennesse OELs: Skin designation

BUTOXYETHANOL (CAS 111-76-2)

DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS Can be absorbed through the skin. 34590-94-8)

US ACGIH Threshold Limit Values: Skin designation

DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS Can be absorbed through the skin. 34590-94-8)

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

BUTOXYETHANOL (CAS 111-76-2) Can be absorbed through the skin. DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS Can be absorbed through the skin. 34590-94-8)

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

BUTOXYETHANOL (CAS 111-76-2) Can be absorbed through the skin. DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS Can be absorbed through the skin. 34590-94-8)

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing. Other

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Clear. Liquid. **Appearance**

Liquid. Physical state **Form** Liquid. Light blue Color Lemon Odor Not available. **Odor threshold**

Ha 11 - 12

Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

Flash point Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper (%)

Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

0.00001 hPa estimated Vapor pressure

Not available. Vapor density Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 8.90 lbs/gal estimated
Percent volatile 87.57 % estimated

Pounds per gallon8.9 lb/galSpecific gravity1.07 estimatedVOC (Weight %)5 % estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

IngestionExpected to be a low ingestion hazard.InhalationProlonged inhalation may be harmful.

Skin contact Causes skin irritation.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Not available.

Product Species Test Results

Water Extraction Carpet Cleaner (CAS Mixture)

Acute

Dermal

LD50 Rabbit 11764.7061 mg/kg estimated

Inhalation

LC50 Mouse 20588.2344 ppm, 7 Hours estimated

Rat 13235.2939 ppm, 4 Hours estimated

Oral

LD50 Mouse 35.2941 g/kg estimated

Rat 10674.4863 mg/kg estimated

337.5 ml/kg estimated

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Material name: Water Extraction Carpet Cleaner 1414 Version #: 01 Issue date: 12-31-2014

^{*} Estimates for product may be based on additional component data not shown.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

BUTOXYETHANOL (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Fish

Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful. May be harmful if absorbed through skin.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

6967.2485 mg/l, 96 hours estimated

prolonged. These effects have not been observed in humans.

12. Ecological information

Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected. **Ecotoxicity**

Product Test Results Water Extraction Carpet Cleaner (CAS Mixture) **Aquatic** Crustacea EC50 Daphnia 1032 mg/l, 48 hours estimated

Persistence and degradability No data is available on the degradability of this product.

Fish

Bioaccumulative potential No data available. Partition coefficient n-octanol / water (log Kow)

BUTOXYETHANOL 0.83

LC50

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

^{*} Estimates for product may be based on additional component data not shown.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

This substance/mixture is not intended to be transported in bulk.

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200. All components are listed or exempted from listing on the U.S. EPA

TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

BUTOXYETHANOL (CAS 111-76-2) Listed. POTASSIUM HYDROXIDE (CAS 1310-58-3) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
BUTOXYETHANOL	111-76-2	3 - < 5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

BUTOXYETHANOL (CAS 111-76-2)

DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS 34590-94-8)

POTASSIUM HYDROXIDE (CAS 1310-58-3)

US. New Jersey Worker and Community Right-to-Know Act

BUTOXYETHANOL (CAS 111-76-2)

DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS 34590-94-8)

POTASSIUM HYDROXIDE (CAS 1310-58-3)

US. Pennsylvania Worker and Community Right-to-Know Law

BUTOXYETHANOL (CAS 111-76-2)

DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS 34590-94-8)

POTASSIUM HYDROXIDE (CAS 1310-58-3)

US. Rhode Island RTK

BUTOXYETHANOL (CAS 111-76-2)

POTASSIUM HYDROXIDE (CAS 1310-58-3)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

16. Other information, including date of preparation or last revision

Issue date 12-31-2014

Version # 01

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.